

Mini thermometer with penetration probe



Measures temperatures in laboratories, food industry, HVAC sector, gardening centres, offices etc.

The affordable mini thermometer with Min/Max alarm. Small in size but big on quality! The penetration probe is attached to the instrument (80 cm cable) and is suitable for measuring the temperature in air, in soft, powdery substances and in liquids.

- **Permanently attached probe**
- **Adjustable Min/Max alarm**
- **Integrated clip for attachment to clothing, wall, placing in position**

Ordering data/Quantity discount

Mini thermometer, from 5 off

Mini thermometer, from 10 off

Mini thermometer, from 25 off

Mini thermometer, from 50 off

ISO calibration certificate/Temperature
For air/immersion probes, calibration point -18°C

Part no. 0520 0061

ISO calibration certificate/Temperature
For air/immersion probes, calibration point 0°C

Part no. 0520 0062

Technical data

Meas. range	-50... +150 °C
Accuracy	±1 °C (-10... +100 °C) ±2 °C (-50... -10.1 °C) ±2 °C (+100.1... +150 °C)
Resolution	0.1 °C (-19.9... +150 °C) 1 °C (-50... -20 °C)
Oper. temp.	0... +50 °C
Storage temp.	-20... +70 °C
Battery type	2 AAA micro batteries
Battery life	100 h
Length/Probe stem	190 mm
Diameter/Probe stem	Ø 3 mm
Warranty	2 years

Mini thermometer

Mini thermometer, battery included

Part no. 0900 0530



Flexible probe
MAX/MIN
-50 to +150°C

Thermometer with robust penetration probe



Measures core temperature of chickens, for example, just prior to being served

The compact testo 915-1 thermometer has many advantages including a large display, hold button and high accuracy. The probe is particularly suitable for immersion and penetration measurements in the food sector.

- **Compact instrument with permanently attached probe**
- **TopSafe protects instrument from dust, dirt and water**
- **With calibration protocol**

Ordering data for Accessories

TopSafe (indestructible protection case) with bench stand

Part no. 0516 0188

Case for instrument and probes
For safe and orderly storage

Part no. 0516 0182

ISO calibration certificate/Temperature
For air/immersion probes, calibration points -18°C; 0°C

Part no. 0520 0041

ISO calibration certificate/Temperature
For air/immersion probes, calibration points 0°C; +60°C

Part no. 0520 0042

Technical data

Meas. range	-50... +400 °C
Accuracy	±1% of mv (+100.1... +400 °C) ±1 °C (-50... +100 °C)
Resolution	0.1 °C (-50... +400 °C)
Oper. temp.	0... +50 °C
Storage temp.	-20... +70 °C
Battery type	Alkali manganese
Battery life	500 h
Auto Off	10 min
Length/Probe stem	110 mm
Diameter/Probe stem	Ø 4 mm
Warranty	2 years



Flexible probe
HOLD
-50 to +400°C



testo 915-1

testo 915-1, thermometer with penetration probe and battery

Part no. 0560 9151